

LHS3120LXP3




ELECTROZEMPER S.A.
Avda. de la Ciencia s/n.
Parque Ind. Avanzado
13005 Ciudad Real. Spain.
Tel.: +34 902 11 11 97
Fax: +34 902 11 11 97
in fo @ ze m p e r . c o m
w w w w . z e m p e r . c o m

Graphic reference

HARENA



Dimensions



Control System: AutoTest

Luminaire: Self-Contained

Standards: EN-60598-1, EN-60598-2-22, EN-62034

Certification: CE

Electrical characteristics

Supply: 230V 50Hz<4.0W

 $\label{eq:maintained} \begin{tabular}{ll} \textbf{Maintained mode consumption: 4,0 W} \\ \textbf{Non-maintained mode consumption: -W} \\ \end{tabular}$

Working temperature: 0-40°C

Emergency lamp: 8xLEDS 0.5W+2xLEDS 3W

Emergency lumen output: 120 lm Maintained lumen output: 70 lm Battery: 3.2V-3.0Ah LFP Class: II Mode: M

Power factor: - % Signaling Luminaire: -LED temperature: 4000°K

Duration: 3 h Remote control: Yes Charging time: 12 h

Mechanical characteristics

Housing: Polycarbonate

Diffuser: Methacrylate

Suitable for flammable surfaces: Yes

IP/IK: IP42/IK04

Finish: Grey RAL9006

Weight: 0,78KG

ATEX Envelope:

Photometric curve

Interdistance

Installation height		
2,0 m	6,93 m	6,20 m
2,5 m	7,69 m	7,06 m
3,0 m	8,30 m	7,77 m
3,5 m	8,77 m	8,34 m



LHS3120LXP3



ELECTROZEMPER S.A.
Avda. de la Ciencia s/n.
Parque Ind. Avanzado
13005 Ciudad Real. Spain.
Tel.: +34 902 11 11 97
Fax: +34 902 11 11 97
in fo@zemper.com

Installation characteristics

HARENA

Insta	lla	ation	with	m	าดเ	ıntiı	ng	plate.
_								

Possibility of installation in:

Ceiling surface.

Wall mural.

Wall flag.

Possibility of connection with:

Surface tube wiring.

Vision distance: 25,8 m

Operating characteristics

The luminaire has status LEDs, which indicates:

Status of the battery charging circuit.

Battery status (duration)

Emergency status function.

Test status.

Microprocessor controlled luminaire that performs periodic and automatic tests.

Functional test every 7 days.

Duration test every 365 days.

The test result is shown in the status indicator LEDs.

Remote control input that allows:

Put on Standby without power supply.

Restart in emergency status without power supply.

Switch on in emergency status (more than 24 h of charge)

Manual and remote duration test. (more than 24 hours of charge).

Date and time programming of the tests.

Reset of the luminaire status.

General Envelope data	



LHS3120LXP3



ELECTROZEMPER S.A.
Avda. de la Ciencia s/n.
Parque Ind. Avanzado
13005 Ciudad Real. Spain.
Tel.: +34 902 11 11 97
Fax: +34 902 11 11 97
in fo@zemper.com
www.zemper.com

Accessories

HARENA







