

Graphic reference



Dimensions

General Dimensions (mm)				
Atex enclosure	a	b	c	d
E1	485	375	157	173
E2	750	640	157	173
E3	1360	1250	157	173

Control System: DALI **Luminaire:** Self-Contained

Standards: EN 60079-0 / EN 60079-1 / EN 60079-31 **Certification:** CE, IECEx INE 21.0022X, INERIS21ATEX0012CY


Electrical characteristics

Supply: 220-240V 50-60Hz<45.0W	Class: I
Maintained mode consumption: 45.0 W	Mode: M/NM
Non-maintained mode consumption: - W	Power factor: - %
Working temperature: 0°C<=Ta<=+50°C	Signaling Luminaire: 220-240Vac<45.0W
Emergency lamp: LEDS	LED temperature: 4000°K
Emergency lumen output: 750 lm	Duration: 3 h
Maintained lumen output: 4750 lm	Remote control: Yes
Battery: 3,2V-9,0Ah LFP	Charging time: 12 h

Mechanical characteristics

Envelope: Aluminum	IP/IK: IP66/IK10
Diffuser: Transparent Polycarbonate	Finish: Transparent
Suitable for flammable surfaces: Yes	ATEX: Yes
ATEX Protection: Zona 1/Zona 21/Ex db IIC T6 Gb/Ex tb IIIC T85°C Db	Weight: 10,90KG
ATEX Envelope: E3	

Photometric curve



Interdistance

Installation height	Interdistance (Left)	Interdistance (Right)
2,0 m	12,79 m	9,92 m
2,5 m	14,95 m	11,56 m
3,0 m	16,00 m	12,47 m
3,5 m	16,88 m	13,43 m

Installation characteristics

Electrical connection by 5-pole + T connector for cable up to 2.5 mm².

The maintained luminaires have the possibility of connection to enable / disable the maintained mode.

Possibility of installation in:

- Ceiling/Wall surface with clamping flanges.

- Suspended roof, with eyebolt.

Possibility of connection with:

- Surface tube wiring.

Two 3/4" NPT entries for cable glands (not included), one of which is provided with a plug.

Operating characteristics

Bus available for DALI communication.

The luminaire has a status LED, which indicates:

- Green LED: OK

- Yellow LED flashing: Battery charging or battery connection failure.

- LED off: Emergency operation failure or mains failure or defective LED or defective unit.

General Envelope data

Tubular diffuser:

- Borosilicate glass, E1 (7mm thick) E2/E3 (9mm thick)

- Polycarbonate, UV protected. 3mm thick.

Casting & connections:

- Aluminum injection

- Manufactured from marine grade aluminum alloy copper free

- Yellow RAL-1003 polyurethane paint

- Explosion proof O-ring.

- 2 entries 3/4" NPT for cable glands (not included)

- 1 plug supplied

- Electric connection through 5P+T 2,5 mm² terminal block

- Suitable for installation on flammable surfaces

Accessories

BRD001



ACC. FLANGE FOR SURF. SATURNO
CEILING MOUNTING

CAM-001



RING BOLT FOR PENDANT MOUNTING

PSA001



ACC. CABLE GLANDS SATURNO
METALLIC

APS016



ACC. PICTO. SATURNO LEFT
ARROW

APS017



ACC. PICTO. SATURNO RIGHT
ARROW

APS019



ACC. PICTO. SATURNO DOWN
ARROW