


### Graphic reference



### Dimensions



**Control System:** DALI

**Luminaire:** Self-Contained

**Standards:** EN-60598-1,  
EN-60598-2-22, EN-62034

**Certification:** CE



### Electrical characteristics

**Supply:** 230V 50Hz<3.6W

**Maintained mode consumption:** 3.6 W

**Non-maintained mode consumption:** - W

**Working temperature:** 0-40°C

**Emergency lamp:** 8xLEDS 0.5W

**Emergency lumen output:** - lm

**Maintained lumen output:** - lm

**Battery:** 3.2V-1.5Ah LFP

**Class:** II

**Mode:** M

**Power factor:** - %

**Signaling Luminaire:** -

**LED temperature:** 4000°K

**Duration:** 3 h

**Remote control:** Yes

**Charging time:** 12 h

### Mechanical characteristics

**Envelope:** Polycarbonate

**Diffuser:** Methacrylate

**Suitable for flammable surfaces:** Yes

**ATEX Envelope:**

**IP/IK:** IP42/IK04

**Finish:** White RAL9003

**Weight:** 0,50KG

### Photometric curve



### Interdistance

Installation height	Diagram 1	Diagram 2
2,0 m	-	-
2,5 m	-	-
3,0 m	-	-
3,5 m	-	-

### Installation characteristics

Maintained luminaires use 3 terminals to enable / disable the maintained mode.

Luminaires made up of a spotlight + electrical equipment with batteries.

Possibility of installation in:

Recessed ceiling.

Ceiling fixing by 2 springs.

Vision distance: 25,8 m

Two type of pictograms (according to reference):

Man with arrow up/down : ref LSS\*\*\*6\*\*\*

Man with arrow right/left : ref LSS\*\*\*5\*\*\*

### Operating characteristics

Bus available for DALI communication.

The luminaire has a status LED, which indicates:

Green LED: OK

Yellow LED flashing: Battery charging or battery connection failure.

LED off: Emergency operation failure or mains failure or defective LED or defective unit.

### General Envelope data