

30° - 120 30° - 140 160

# LUZ4150LXP3



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo @ zem per.com w w w.zem per.com

Graphic reference	Dimensions
	d∋s106
	Control System: AutoTest Luminaire: Self-Contained
	Standards: EN-60598-1, Certification: CE, ENEC,
	EN-60598-2-22, EN-62034 KITEMARK, CIVIL DEFENSE
Electrical characteristics	
Supply: 230V 50Hz<2.5W Maintained mode consumption: 2,5 W	Class: II Mode: Non-maintained / Maintained via third terminal
Non-maintained mode consumption: 0,9 W	Power factor: - %
Working temperature: 0-40°C	Signaling Luminaire: -
Emergency lamp: 12xLED 0.5W Emergency lumen output: 150 lm	LED temperature: 4000°K Duration: 3 h
Maintained lumen output: 95 lm	Remote control: No
Battery: 3.2V-1.5Ah LFP	Charging time: 12 h
Mechanical characteristics	
Housing: Polycarbonate	<b>IP/IK:</b> IP42/IK04
Diffuser: Transparent Polycarbonate	Finish: White RAL9003
Suitable for flammable surfaces: Yes	
	Weight: 0,19KG
ATEX Envelope:	
Photometric curve	Interdistance
	7
	Installation height $7,44 \text{ m}$ $7,43 \text{ m}$
90°	
49	2,5 m 8,15 m 8,15 m
60° 60°	3,0 m 8,72 m 8,72 m

3,5 m

9,18 m

9,18 m



### LUZ4150LXP3



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo@zemper.com www.zemper.com

#### Installation characteristics

Non-maintained luminaires use 4 terminals (2xL + 2xN) for supply connection. Maintained luminaires use 5 terminals (2xL + 2xN + L1) to enable / disable the maintained mode. Installation with mounting plate. Possibility of installation in: Ceiling/Wall surface. Recessed ceiling (with installation accessory) Possibility of connection with: Recessed wiring. Surface tube wiring (max. M20)

#### **Operating characteristics**

The luminaire has status LEDs, which indicates:
Status of the battery charging circuit.
Battery status (duration)
Emergency status function.
Test status.
Microprocessor controlled luminaire that performs periodic and automatic tests.
Functional test every 7 days.
Duration test every 365 days.
The test result is shown in the status indicator LEDs.
The luminaire has a built-in button, which allows:
Simulation test of supply failure.

#### General Envelope data



## LUZ4150LXP3

ALC0011



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo @ z em per.com w w w.z em per.com

#### Accessories









ACC. PANEL REC. SPAZIO LUZ WHITE



