

## LUZX4400LA



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo @ zem per.com w w w.zem per.com

Graphic reference	Dimensions
	100 60   100 10
Electrical characteristics	
Supply: 230V 50Hz<0.9W Maintained mode consumption: - W Non-maintained mode consumption: 0,9 W Working temperature: 0-40°C Emergency lamp: 12xLED 0.5W Emergency lumen output: 400 lm Maintained lumen output: - Im Battery: 3.2V-1.5Ah LFP	Class: II Mode: NM Power factor: - % Signaling Luminaire: - LED temperature: 4000°K Duration: 1 h Remote control: Yes Charging time: 12 h
Mechanical characteristics	
Housing: Polycarbonate Diffuser: Transparent Polycarbonate Suitable for flammable surfaces: Yes	IP/IK: IP42/IK04 Finish: White RAL9003 Weight: 0,16KG
ATEX Envelope:	
Photometric curve	Interdistance
$90^{\circ}$ $60^{\circ}$ $140$ $60^{\circ}$ $140$ $160$ $160$	Installation height ↓ ↔ ↓ ↓ ↔ ↓   2,0 m 9,80 m 9,78 m   2,5 m 10,98 m 10,96 m   3,0 m 11,92 m 11,91 m   3,5 m 12,74 m 12,73 m



### LUZX4400LA



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo @ z em per.com w w w.z em per.com

#### Installation characteristics

Non-maintained luminaires use 4 terminals (2xL + 2xN) for supply connection. Maintained luminaires use 5 terminals (2xL + 2xN + L1) to enable / disable the maintained mode. Installation with mounting plate. Possibility of installation in: Ceiling/Wall surface. Recessed ceiling (with installation accessory) Possibility of connection with: Recessed wiring. Surface tube wiring (max. M20)

#### **Operating characteristics**

Bus available for DALI2 communication.

The luminaire has a status LED, which indicates:

Green LED: OK

Yellow LED flashing: Battery charging or battery connection failure.

LED off: Emergency operation failure or mains failure or defective LED or defective unit.

#### General Envelope data



## LUZX4400LA



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo @ z em per.com w w w.z em per.com

# ALQ0011 ACC. REC. SPAZIO LUZ WHITE CEILING SQUARE ALX0011 ACC. REC. PANEL SPAZIO LUZ WHITE CEILING SQUARE ALS0011



