

- CO - C180

C90 - C270

## LXEX9400LW



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel:: +34 902 11 11 97 Fax: +34 902 11 11 97 info@zemper.com www.zemper.com





### LXEX9400LW



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel:: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo@zemper.com www.zemper.com

#### Installation characteristics

Maintained luminaires have a selector bridge to enable / disable the maintained mode. Possibility of installation in: Ceiling/Wall surface. Possibility of connection with: Surface tube wiring. It has 3 pre-marked entries for PG-11 cable glands (not included), for mounting with surface pipe.

#### **Operating characteristics**

The luminaire has status LEDs, which indicates:
Status of the battery charging circuit.
Battery status (duration)
Emergency status function.
Test status.
Microprocessor controlled luminaire
The luminaire can be connected to a control unit.
When the luminaire is installed without a control unit, it performs periodic and automatic tests.
Functional test every 7 days.
Duration test every 365 days.
The test result is shown in the status indicator LEDs.
Wireless communication that allows: Communication with Control unit by wireless communication with a 2.4Ghz frequency system.

#### General Envelope data



# LXEX9400LW



ELECTROZEMPER S.A. Avda. de la Ciencia s/n. Parque Ind. Avanzado 13005 Ciudad Real. Spain. Tel.: +34 902 11 11 97 Fax: +34 902 11 11 97 in fo @ zemper.com w w w.zemper.com

Accessories

APF600

